

Flocon® 260 - Premium Antiscalant and Antifoulant for Membrane Systems



Product Description

Flocon 260 is an aqueous solution of a specialized polycarboxylic acid, highly effective in controlling the deposition of inorganic scale forming salts and particulate fouling on membrane surfaces.

- Excellent control of carbonate scales, sulphate and fluoride for cost effective operation
- Effectively control both soluble and insoluble iron
- Effective against silica fouling
- Dispersant
- Compatible with all major membranes
- International potable water approvals

Typical Properties

The following are typical properties for Flocon 260 and should not be regarded as specification limits for the product. A product specification is available on request.

Appearance	pale yellow liquid
pH	< 2
Specific gravity at 20/20°C	1.14 to 1.165
Freezing point range	0 to -10°C

Chemical Reactivity

Flocon 260 is not affected by chlorine or other oxidising biocides under normal conditions of use. Flocon 260 may be used in membrane systems using chlorine and sodium metabisulphite.

Application and Dose Level

Flocon 260 is an aqueous solution of an organic acid and as such is corrosive in its concentrated form. Corrosion resistant dosing equipment should therefore be used. Examples of suitable materials are 316L stainless steel, or plastics such as GRP, PVC and PE.

The recommended injection point is into the feed water downstream of any filtration equipment and cartridge filters.

Flocon 260 is miscible with water in all proportions. It may be applied as the neat product, or as a solution in permeate. A minimum dosing solution strength of 10% w/w is recommended. Flocon 260 should be dosed continuously and proportionately to the feed water flow, to maintain the recommended dose level.

The dose level required is dependent on the quality of the feedwater and the saturation indices of the various scale forming species present in the concentrated brine. Proprietary computer software is used to calculate scaling indices and calculate optimum system recovery. Dose level projections and recommendations are available on request.

Handling

Flocon 260 is certified to ANSI / NSF Standard 60 for use in reverse osmosis systems producing potable water.

Please read the label and Material Safety Data Sheet before handling this product.

Logistics

Classification Hazardous for transportation, class 8
Irritating to eyes for supply

Part Number	Description	Net Weight
FLO260-6	Plastic drums	55 lbs
FLO260-55	Plastic drums	507 lbs
FLO260-275	Intermediate Bulk Containers	2205 lbs

